

Revision Date: 02/01/2021

# SAFETY DATA SHEET

# 1. Identification

Material name: TO ALPHAGUARD PUMA QUICK FLASH 2 GL

Material: 351950 802

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco CPG Inc. - U.S. Roofing

3735 Green Road Beachwood OH 44122

US

**Contact person:** EH&S Department **Telephone:** 216-292-5000

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

#### **Hazard Classification**

#### **Physical Hazards**

Flammable liquids Category 1

#### **Health Hazards**

Acute toxicity (Inhalation - dust and

mist)

Category 4

Serious Eye Damage/Eye Irritation Category 2A Skin sensitizer Category 1

# **Unknown toxicity - Health**

Acute toxicity, oral 4.75 %
Acute toxicity, dermal 26.05 %
Acute toxicity, inhalation, vapor 74.35 %
Acute toxicity, inhalation, dust 80.7 %

or mist

#### **Label Elements**

# **Hazard Symbol:**



Revision Date: 02/01/2021



Signal Word: Danger

**Hazard Statement:** Extremely flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

workplace.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label).

Wash contaminated clothing before reuse. In case of fire: Use... to

extinguish.

**Storage:** Store in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged

even in bonded and grounded equipment.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	15 - 40%
Aluminum hydroxide	21645-51-2	15 - 40%
Barium sulfate	7727-43-7	15 - 40%



Revision Date: 02/01/2021

Silicon dioxide, amorphous 112945-52-5	1 - 5%
--	--------

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

#### Description of necessary first-aid measures

**Inhalation:** Move to fresh air.

**Skin Contact:** Get medical attention if symptoms occur. Take off immediately all

contaminated clothing. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic

skin reaction develops, get medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

**Ingestion:** Rinse mouth thoroughly.

**Personal Protection for First-**

aid Responders:

Firefighters must use standard protective equipment including flame

retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

**Symptoms:** Respiratory tract irritation.

**Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Get medical attention if symptoms occur.

#### 5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters



Revision Date: 02/01/2021

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

# 7. Handling and storage

#### Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Safe handling advice:

Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal

protective equipment. Observe good industrial hygiene practices.

Contact avoidance measures: No data available.

**Hygiene measures:** Avoid contact with eyes. Observe good industrial hygiene practices. When

using do not smoke. Contaminated work clothing should not be allowed out

of the workplace. Avoid contact with skin.

**Storage** 

**Safe storage conditions:** Store in a well-ventilated place. Store in a cool place.

**Safe packaging materials:** No data available.

#### 8. Exposure controls/personal protection

#### **Control Parameters**



Revision Date: 02/01/2021

**Occupational Exposure Limits** 

Chemical Identity	Туре	Exposure Limit Values	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Methyl methacrylate	PEL	100 ppm 410 mg/m3	
	TWA	50 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	100 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
Aluminum hydroxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)
Silicon dioxide, amorphous	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (2000)

Chemical name	Туре	Exposure Limit Values	Source
Methyl methacrylate	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)



Revision Date: 02/01/2021

Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Barium sulfate - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Barium sulfate - Inhalable	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Aluminum hydroxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum hydroxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** Additional Information: Use suitable protective gloves if risk of skin contact.

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.



Revision Date: 02/01/2021

**Hygiene measures:** Avoid contact with eyes. Observe good industrial hygiene practices. When

using do not smoke. Contaminated work clothing should not be allowed out

of the workplace. Avoid contact with skin.

# 9. Physical and chemical properties

**Appearance** 

Physical state:liquidForm:liquidColor:Gray

Odor: Mild petroleum/solvent
Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: 11.5 °C 52.7 °F(ISO 1516 (Pensky-Martens (A and B Closed

Cup)))

**Evaporation rate:** Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

No data available.

No data available.

Explosive limit - lower:

No data available.

Vapor pressure: 38.7 mbar (20 °C 68 °F)

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.36

Solubility(ies)

Solubility in water: Practically Insoluble
Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

# 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.



Revision Date: 02/01/2021

Incompatible Materials: Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides

and chromates). Strong bases.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

# Information on likely routes of exposure

**In high concentrations**, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** May cause an allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

# Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

Oral

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate LD 50 (Rat): 7,900 mg/kg

Aluminum hydroxide LD 50 (Rat): > 2,000 mg/kg

Barium sulfate LD 50 (Rat): 307 g/kg

Dermal

**Product:** ATEmix: 7,663.21 mg/kg

Inhalation

**Product:** ATEmix: 2.3 mg/l

Repeated dose toxicity

**Product:** No data available.



Revision Date: 02/01/2021

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):

Methyl methacrylate (Rabbit): Irritating.

in vivo (Rabbit): irritating after 4/24h occluded exposure

in vivo (Rabbit): Not irritant, 24 - 72 h

Aluminum hydroxide in vivo (Rabbit): Not classified as an Irritant, 24 - 72 h

Barium sulfate validated "in vitro" test method Not irritant

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Methyl methacrylate Rabbit, 24 - 72 hrs: Not irritating

Aluminum hydroxide Rabbit, 24 hrs: Not irritating

Barium sulfate Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure** 



Revision Date: 02/01/2021

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

# 12. Ecological information

#### **Ecotoxicity:**

#### Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Methyl methacrylate NOAEL (Oncorhynchus mykiss, 96 h): 40 mg/l Experimental result, Key

study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Methyl methacrylate NOAEL (Daphnia magna, 48 h): 48 mg/l Experimental result, Key study

Barium sulfate EC 50 (Water flea (Daphnia magna), 48 h): 32 mg/l Intoxication

#### Chronic hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

Specified substance(s):

Methyl methacrylate NOAEL (Danio rerio): 9.4 mg/l Experimental result, Key study

**Aquatic Invertebrates** 

Product: No data available.

Specified substance(s):

Methyl methacrylate NOAEL (Daphnia magna): 37 mg/l Experimental result, Key study

**Toxicity to Aquatic Plants** 

**Product:** No data available.



Revision Date: 02/01/2021

# Persistence and Degradability

Biodegradation

**Product:** No data available.

Specified substance(s):

Methyl methacrylate 96 % (28 d) Detected in water. Experimental result, Not specified

30.7 % (28 d) Detected in water. Experimental result, Not specified > 95 % (28 d) Detected in water. Experimental result, Not specified 44 % (33 d) Detected in water. Experimental result, Not specified

> 99 % (2 d) Soil Experimental result, Not specified

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Specified substance(s):

Methyl methacrylate Bioconcentration Factor (BCF): 2 - 6.59 Aquatic sediment Estimated by

calculation, Not specified

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):

Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

**Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

# 14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

11/15



Revision Date: 02/01/2021

UN1866, RESIN SOLUTION, 3, PG II

#### **Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

# 15. Regulatory information

#### **US Federal Regulations**

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

# US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

#### CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Methyl methacrylate 1000 lbs. Barium sulfate 1000 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards

# US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

# **US State Regulations**

# **US. California Proposition 65**

No ingredient requiring a warning under CA Prop 65.

# US. New Jersey Worker and Community Right-to-Know Act

# **Chemical Identity**

Methyl methacrylate Barium sulfate



Revision Date: 02/01/2021

# **US. Massachusetts RTK - Substance List**

#### **Chemical Identity**

Methyl methacrylate Barium sulfate Silicon dioxide, amorphous

# US. Pennsylvania RTK - Hazardous Substances

# **Chemical Identity**

Methyl methacrylate Barium sulfate Silicon dioxide, amorphous

#### **US. Rhode Island RTK**

# **Chemical Identity**

Methyl methacrylate

# International regulations

#### **Montreal protocol**

Not applicable

#### Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

# **Kyoto protocol**

Not applicable

#### VOC:

Regulatory VOC (less water and : 0 g/l

exempt solvent)

VOC Method 310 : 0.00 %



Revision Date: 02/01/2021

**Inventory Status:** 

Australia AICS: One or more components in this

product are not listed on or exempt

from the Inventory.

Canada DSL Inventory List:

One or more components in this

product are not listed on or exempt

from the Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are

listed on or exempt from the

Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

New Zealand Inventory of Chemicals: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.



Revision Date: 02/01/2021

# 16.Other information, including date of preparation or last revision

**Revision Date:** 02/01/2021

Version #: 2.1

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.