

# SAFETY DATA SHEET

## 1. Identification

**Material name:** Sheeting Bond Black  
**Material:** 361582 803

### Recommended use and restriction on use

**Recommended use:** Coatings  
**Restrictions on use:** Not known.

### Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing  
3735 Green Road  
Beachwood OH 44122  
US

**Contact person:** EH&S Department  
**Telephone:** 216-292-5000  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Serious Eye Damage/Eye Irritation	Category 2B
Carcinogenicity	Category 2
Toxic to reproduction	Category 2

#### Unknown toxicity - Health

Acute toxicity, oral	12.31 %
Acute toxicity, dermal	12.4 %
Acute toxicity, inhalation, vapor	99.74 %
Acute toxicity, inhalation, dust or mist	99.4 %

### Environmental Hazards

Acute hazards to the aquatic environment	Category 2
--	------------

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment	73.7 %
Chronic hazards to the aquatic environment	100 %

### Label Elements

**Hazard Symbol:**



**Signal Word:** Warning

**Hazard Statement:** Causes eye irritation.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
Toxic to aquatic life.

**Precautionary Statements**

**Prevention:** Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Hazard(s) not otherwise classified (HNOC):** None.

### 3. Composition/information on ingredients

**Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	15 - 40%
Xylene	1330-20-7	15 - 40%
Amorphous silica	7631-86-9	7 - 13%
Ethylbenzene	100-41-4	3 - 7%
Toluene	108-88-3	0.1 - 1%
Talc	14807-96-6	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

**Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

**Most important symptoms/effects, acute and delayed**

**Symptoms:** May cause skin and eye irritation.

**Indication of immediate medical attention and special treatment needed**

**Treatment:** Symptoms may be delayed.

**5. Fire-fighting measures**

**General Fire Hazards:** No unusual fire or explosion hazards noted.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** No data available.

**Methods and material for containment and cleaning up:** Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

**7. Handling and storage**

**Precautions for safe handling:** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities:** Store locked up.

**8. Exposure controls/personal protection**

**Control Parameters**

**Occupational Exposure Limits**

Chemical Identity	Type	Exposure Limit Values	Source
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m <sup>3</sup>	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Amorphous silica	TWA		20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		0.8 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Toluene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
Talc - Respirable fraction.	TWA		2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Talc	TWA		20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Talc - Respirable.	TWA		2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		0.1 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

Chemical name	Type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m <sup>3</sup>	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m <sup>3</sup>	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Amorphous silica - Total	TWA		4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA		1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA		6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Toluene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm	188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Talc - Respirable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc	TWA		2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc - Respirable fraction.	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Talc - Respirable dust.	TWA		3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

### Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)
Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEI (03 2013)
Toluene (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEI (03 2013)

Toluene (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEI (03 2013)
---	-------------------	---------------------

**Appropriate Engineering Controls**      Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Individual protection measures, such as personal protective equipment**

- General information:**      Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
- Eye/face protection:**      Wear safety glasses with side shields (or goggles).
- Skin Protection**
  - Hand Protection:**      Use suitable protective gloves if risk of skin contact.
  - Other:**      Wear suitable protective clothing.
- Respiratory Protection:**      In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:**      Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

<b>9. Physical and chemical properties</b>
--

**Appearance**

- Physical state:**      solid
- Form:**      Paste
- Color:**      Black
- Odor:**      Mild petroleum/solvent
- Odor threshold:**      No data available.
- pH:**      No data available.
- Melting point/freezing point:**      No data available.
- Initial boiling point and boiling range:**      No data available.
- Flash Point:**      > 93 °C > 199 °F
- Evaporation rate:**      Slower than Ether
- Flammability (solid, gas):**      No
- Upper/lower limit on flammability or explosive limits**
  - Flammability limit - upper (%):**      No data available.
  - Flammability limit - lower (%):**      No data available.
  - Explosive limit - upper (%):**      No data available.
  - Explosive limit - lower (%):**      No data available.
- Vapor pressure:**      No data available.

---

<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.158
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Practically Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

**10. Stability and reactivity**

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	No data available.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**11. Toxicological information****Information on likely routes of exposure**

<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin. Causes mild skin irritation.
<b>Eye contact:</b>	Causes eye irritation.
<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.

**Symptoms related to the physical, chemical and toxicological characteristics**

<b>Inhalation:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.
<b>Ingestion:</b>	No data available.



**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)****Oral****Product:** ATEmix: 12,015.09 mg/kg**Dermal****Product:** ATEmix: 4,388.74 mg/kg**Inhalation****Product:** Not classified for acute toxicity based on available data.**Specified substance(s):**

Asphalt LC 50 (Rat): &gt; 94.4 mg/m3

Amorphous silica LC 50 (Rat): &gt; 2.08 mg/l

Toluene LC 50 (Rat): 25.7 mg/l

**Repeated dose toxicity****Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Specified substance(s):**

Asphalt in vivo (Rabbit): Not irritant Experimental result, Key study

Xylene in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study

Amorphous silica in vivo (Rabbit): Not irritant Experimental result, Key study

Toluene in vivo (Rabbit): Irritating Experimental result, Key study

**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Asphalt Rabbit, 24 hrs: Not irritating

Xylene Rabbit, 24 hrs: Moderately irritating

Amorphous silica	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Toluene	Rabbit, 24 - 72 hrs: Not irritating

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** Suspected of causing cancer.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Asphalt	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Talc	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**  
**Product:** No data available.

**In vivo**  
**Product:** No data available.

**Reproductive toxicity**

**Product:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

<b>12. Ecological information</b>
-----------------------------------

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Toluene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 20.5 - 23.8 mg/l Mortality

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Toluene	LC 50 (Water flea (Daphnia magna), 24 h): 240 - 420 mg/l Mortality

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Asphalt	NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
Toluene	LOAEL (Oncorhynchus kisutch, 40 d): 2.77 mg/l Experimental result, Key study NOAEL (Pimephales promelas, 32 d): 4 mg/l Experimental result, Supporting study LOAEL (Pimephales promelas, 32 d): 6 mg/l Experimental result, Supporting study NOAEL (Oncorhynchus kisutch, 40 d): 1.39 mg/l Experimental result, Key study

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**  
**Product:** No data available.

## Persistence and Degradability

**Biodegradation**  
**Product:** No data available.

**BOD/COD Ratio**  
**Product:** No data available.

## Bioaccumulative potential

**Bioconcentration Factor (BCF)**  
**Product:** No data available.

**Specified substance(s):**  
Toluene Green algae (*Selenastrum capricornutum*), Bioconcentration Factor (BCF): 3,016 (Static)

## Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

**Specified substance(s):**  
Xylene Log Kow: 3.12 - 3.20  
Ethylbenzene Log Kow: 3.15  
Toluene Log Kow: 2.73

**Mobility in soil:** No data available.

**Other adverse effects:** Toxic to aquatic organisms.

## 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

## 14. Transport information

### TDG:

Not Regulated

### CFR / DOT:

Not Regulated

**IMDG:**

Not Regulated

## 15. Regulatory information

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Benzene	10 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

Immediate (Acute) Health Hazards

Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Benzene	10 lbs.

### SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Asphalt	10000 lbs
Xylene	10000 lbs
Amorphous silica	10000 lbs
Ethylbenzene	10000 lbs
Toluene	10000 lbs
Talc	10000 lbs

### SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**  
None present or none present in regulated quantities.

### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

### US State Regulations

#### US. California Proposition 65



**WARNING**  
Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

#### US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
Asphalt
Xylene
Amorphous silica
Ethylbenzene
Talc

#### US. Massachusetts RTK - Substance List

<u>Chemical Identity</u>
Asphalt
Xylene
Amorphous silica
Ethylbenzene

#### US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u>
Asphalt
Xylene
Amorphous silica
Ethylbenzene

## US. Rhode Island RTK

### Chemical Identity

Asphalt  
Xylene  
Ethylbenzene

## International regulations

### Montreal protocol

Not applicable

### Stockholm convention

Not applicable

### Rotterdam convention

Not applicable

### Kyoto protocol

Not applicable

### VOC:

Regulatory VOC (less water and  
exempt solvent) : 300 g/l

VOC Method 310 : 25.93 %

**Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.

**16. Other information, including date of preparation or last revision**

<b>Revision Date:</b>	07/21/2018
<b>Version #:</b>	1.4
<b>Further Information:</b>	No data available.



**Disclaimer:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

