

LEED DATA SHEET

DATE:	
PROJECT NAME:	
PROJECT LOCATION:	
NAME OF PRODUCT:	TPA LV Single Ply Bonding Adhesive
DESCRIPTION:	A Low VOC Adhesive Used with the TPA Single Ply Membrane
PRODUCT/MATERIAL COST: \$	

SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	N/A
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	N/A

RECYCLED CONTENT

PRE-CONSUMER:	0	%
POST CONSUMER:	0	%

REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:

		DISTANCE FROM PROJECT:		MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:		MILES
LOCATION OF MANUFACTURE:		DISTANCE FROM PROJECT:		MILES

LOW EMITTING MATERIALS:

COATING VOC <small>(GRAMS/L)</small>	SEALANT VOC <small>(GRAMS/L)</small>	ADHESIVE VOC <small>(GRAMS/L)</small>	USE OF MATERIAL
		194 g/L	

RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:	0	%
COST:	\$	

PREPARED BY:	
--------------	--

**Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.
 **Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.*